# D25 SERIES





The thirst quenchers!





- ✓ The newest addition to the Waterworks<sup>™</sup> range
- ✓ Available in Black or White, with a satin finish
- ✓ Connects to mains water supply
- ✓ Hot & Cold or Cool & Cold models available
- ✓ Large 11L Cold Tank
- ✓ Compatible with most Inline Filter Systems
- ✓ Easy to clean and sanitise
- 36 Month ComprehensiveWarranty

3 YEAR WARRANTY

## D25 SERIES

#### **GENERAL FEATURES**

The D25 series is the latest addition to our range of POU water coolers. With its elegant satin finish, the D25 is sure to add a touch of class to any home or office.

**COLD TANK:** Huge 11 litre high density polypropylene tank. The tank is tough, rustproof and is easy to clean with its large radius.

**HOT TANK:** 1.6 litre type 304 stainless steel with 500 watt sheathed heater ensures temperature control. On/off switch is easily accessible at the back of the unit.

**CABINET:** Satin black or white. Top and front panels are moulded UV treated ABS. Zinc coated steel side panels.

**TAPS:** NSF approved and hygienic durable polypropylene push taps with self-closing design and fast flow. Hot safety tap comes as standard on hot/cold model.

**FLOAT ASSEMBLY:** Dual float system maintains the water level and shuts water off when tank is full.

#### **OPTIONAL EXTRAS**

PNP FILTER SYSTEM: The Waterworks™ PNP filter range is available in single, twin or triple. With the swing & twist design and automatic water shutoff, filter changes are simple, no need for tools or to turn off the mains water.

CD WHITE OR BLACK: Our cup dispensers come in black or white to match either colour unit. Waterworks™ paper & plastic cups are designed to fit our dispensers.

#### INSTALLATION

To be installed in accordance with local plumbing laws. Failure to install a certified Pressure Limiting Valve will void warranty.

#### **SPECIFICATIONS**

**REFRIGERATION:** Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

**ELECTRICAL:** Certificate number 160793. 220v 50hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps.

**CONDENSER:** Quietly operating, air cooled with no moving parts.

#### **PERFORMANCE**

Tap 1 Approx. 4-10°C Tap 2 Room Temperature Hot tap Approx. 84-89°C

#### **CAPACITY**

ROOM TEMP °C	21	27	32			
150ML CUPS/HR 10°C	35	28	16			
LITRES/HR AT 10°C	5.2	4.2	2.4			
HOT WATER DELIVERY: 15 x 170ml cups per hour						

<sup>\*</sup>Intermittent use only, continuous use will result in reduced performance.

#### SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
D25C	21kg	D25CH	23kg	33cm	39cm	115cm

#### **WARRANTY**

The Waterworks™ D25 series is covered by our 36 month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of original sale.



### Waterworks<sup>™</sup> Australia

ABN 91 902 793 936

48-50 Neumann Road Capalaba Queensland 4157 Bulk Warehouse: 53 Neumann Road Capalaba Queensland 4157 Distributed by...

Phone (07) 3390 3777

Email sales@waterworksaustralia.com

www.waterworksaustralia.com