

NOVO SERIES

Mains-Connected or Bottled Water Coolers

Aqua Cooler's Novo range brings the capacity and performance of a premium cooler to an affordable and stylish unit. Available in both mains connected and bottled, the Novo range is perfect for small office or home use.



KEY FEATURES

- Stainless steel side panels and corner pieces for heavier-duty applications
- Individually switched power for heating and cooling circuits
- Durable polypropylene, colour-coded, self-closing taps
- Food-grade, stainless steel water contact tubes
- Easy-to-clean, removable drip tray
- 12 month standard warranty and 36 month compressor warranty
- Full range of replacement parts

These free-standing coolers offer durable polypropylene, self-closing, hot-and-cold taps with a child-safety tap on the hot side.

The Novo range can dispense up to 5 L/h of hot water and 2 L/h of cold. The stainless steel side panels and corner pieces make this unit perfect for heavier-duty applications such as workshops.

Coupled with our twelve month standard warranty, additional twenty-four month refrigeration circuit warranty and full range of replacement parts, the Novo is a sturdy choice for a long-lasting water dispenser.



Model Selection Chart

	Filtered*	Bottled	Mains-Connected
Cook & Cold	Yes	-	NMCCF
	No	NBCC	NMCC
Hot & Cold	Yes	-	NMHCF
	No	NBHC	NMHC

* Filtered models are supplied with filter upgrade kit.

Your Partner in Cool.

AQUA
COOLER

TECHNICAL SPECIFICATIONS

Water Reservoir	Cold	2 L	
	Hot	4 L	
Housing Material	Plastic with stainless steel side panels and corner peices		
Refrigeration	Uses R134A refrigerant		
Water Connections	Water Inlet	¼" quick-connect tube fitting	
Thermostat Control	The thermostat is factory set		
Capacity	Cold	5 L/h	
	Hot	2 L/h	
Power Consumption	Mains-Connected	Cooling	85 W
		Heating	400-800 W
	Bottled	Cooling	100 W
		Heating	400-800 W
Electrical	220-240 V, 50/60 Hz		
Weight (Packed)	Hot & Cold	18 kg	
	Cook & Cold	17 kg	
Dimensions (Packed)	330 x 360 x 1000 mm (W x D x H)		
Container Capacity	Mains-Connected	20 ft	224 units
		40 ft	462 units
	Bottled	20 ft	210 units
		40 ft	434 units
Warranty	Twelve month comprehensive coverage and three year compressor replacement.		

